

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) An electromagnetic field deflecting garment,
comprising:

a conducting fabric edged with a lattice fabric having conductive filaments which
serve to close a conductive circuit between said conducting fabric and said lattice fabric;

5 and

an electronic circuit ~~operably~~ interconnected through a conductor to ~~said
conducting fabric and said lattice fabric to form a closed circuit~~, wherein said electronic
circuit is operable to substantially completely dispel an electromagnetic signal ~~received at
coming from~~ said garment through a Joule effect.

2. (Previously Presented) A garment according to claim 1, wherein said
conducting fabric is a knitted fabric with filaments consisting of conductive material
disposed parallel to each other.

3. (Currently Amended) A garment according to claim 1, wherein said lattice
fabric has filaments of conductive material disposed in a ~~cross-linked~~ lattice wherein at
least one filament of conductive material is arranged in a perpendicular orientation
relative to the remaining filaments of conductive material.

4. (Previously Presented) A garment according to claim 1, wherein said
electronic circuit is a parallel resonator at a predetermined cutting frequency and
predetermined resonance frequency.

5. (Previously Presented) A garment according to claim 4, wherein said parallel
resonator consists of the connection in parallel of an inductance, a first and a second
capacitance decoupled by a diode, and a resistance, said parallel resonator being coupled
to the conductive fabric by means of a coupling capacitance.

6. (Previously Presented) A garment according to claim 5, wherein said inductance is about 10 μ H, the first capacitance is about 20 pF, the second capacitance is about 10 μ F, the diode is the model 1N32A, the resistance is about 2 M Ω and the coupling capacitance is about 100 pF.

7. (Previously Presented) A garment according to claim 1, wherein grounding of the electronic circuit is achieved by means of a cord protruding from the garment and made of conductive material.

8. (Previously Presented) A garment according to claim 1, wherein a microamperometer is connected to said electronic circuit allowing the intensity of the electromagnetic field absorbed by the garment to be displayed.

9. (Previously Presented) A garment according to claim 1, wherein said garment is a jacket.

10. (Previously Presented) A garment according to claim 9, wherein said jacket comprises a housing to hold objects, a housing to contain the microamperometer and a housing to contain the electronic circuit.

11. (Previously Presented) A garment according to claim 1, wherein said garment is a hat.

12. (Previously Presented) A garment according to claim 11, wherein said electronic circuit is positioned inside the hat.

13. (Previously Presented) A garment according to Claim 4, wherein said predetermined cutting frequency is about 7 MHZ.

Application No. 09/555,105

14. (New) A garment according to Claim 1, wherein said electronic circuit is operable to substantially completely dispel said electromagnetic signal independently of any other connections to said garment.